1994	TARIFF NO. 010	9	ORIGINAL ISSUED:	PAGE JANUARY 1,	45	
_		I	EFFECTIVE:	MARCH 31		
	<u>1994</u>					
	SECTION ELEVEN					
	GENERAL INFORMATION					
		FMC SUBRULE: 34-G01				
FOR EXPLANATION OF SYMBOLS, SEE PAGE 0-A (AFTER TITLE PAGE)						

FOR EXPLANATION OF SYMBOLS, SEE PAGE 0-A (AFTER TITLE PAGE)

		ITEM
The prescribed anchorage area for vessels anchoring outside the harbor is located eastward of a line about 1.5 nautical miles off shore and northward of a line about 0.2 nautical miles north of the sea buoy at the entrance to the ship channel. The entire anchorage area lies north of the entrance channel to Miami. The northern and southern extremities of this area are marked by nun buoys. Vessels desiring to anchor off the entrance to the Harbor of Miami are required to do so within this area, to avoid possible damage to cables laid on the ocean bottom in the vicinity. Refer to anchorage area 110.188 on National Oceanic and Atmospheric Administration Survey Chart # 11466 & # 11468.	ANCHORAGE (C)	816
The normal mean tidal range at the entrance to Miami Harbor is 2.5 feet, and in the bay it is about 2.0 feet. The extreme tidal range is about 4.0 feet at the entrance. Easterly winds sometimes raise the water level 1.5 feet at the entrance and from 1.0 to 0.5 feet in the bay.	TIDES AND TIDAL CURRENTS (C)	818
The tidal currents at the entrance to Biscayne Bay may reach a velocity of 1-1/2 to 3 knots through the main channel.		
THIS SPACE INTENTIONALLY LEFT BLANK		

1994	TARIFF NO. 010	ORIGINAL ISSUED: JANI	PAGE 45 UARY 1,			
_		EFFECTIVE: M.	MARCH 31,			
	SECTION ELEVEN GENERAL INFORMATION FMC SI	JBRULE: 34-G01				
FOR EXPLANATION OF SYMBOLS, SEE PAGE 0-A (AFTER TITLE PAGE)						